

Size/ Type	Measureindex	Weight Kg	Description	Diameters cable = DC from 6mm to 28mm resulting cable lengths/ capacity + drum sizes																						
				06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	22	24	26	28				
			<b>Cable Diameters (DC)</b>	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	22	24	26	28				
PV 1.400	400.620.600.300.580.	21,0	Drum Alu for up to zu ¼ EUPAL W x H x D = 400 x 620 x 600 Core diametre.: 300 Outer diametre.: 580	13000	9500	7000	5500	4300	3200	2100	1000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000				
PV 1.500	500.620.600.300.580.	22,8	Drum Alu W x H x D = 500 x 620 x 600 Core diametre.: 300 Outer diametre.: 580	17800	28800	9700	7800	6300	5400	4300	3200	2100	1000	0000	0000	0000	0000	0000	0000	0000	0000	0000				
PV 1.600	600.620.600.300.580.	24,6	Drum Alu W x H x D = 600 x 620 x 600 Core diametre.: 300 Outer diametre.: 580	25500	68400	29700	20700	13000	8400	5400	3200	2100	1000	0000	0000	0000	0000	0000	0000	0000	0000	0000				
PV 1.700	700.620.600.300.580.	26,4	Drum Alu W x H x D = 700 x 620 x 600 Core diametre.: 300 Outer diametre.: 580	32300	91500	38100	25700	16400	10700	6500	4000	2400	1400	800	400	000	000	000	000	000	000	000				
PV 1.800	800.620.600.300.580.	28,2	Drum Alu for up to zu ½ EUPAL W x H x D = 800 x 620 x 600 Core diametre.: 300 Outer diametre.: 580	32100	37400	14100	9700	6100	3900	2400	1400	800	400	000	000	000	000	000	000	000	000	000				
			<b>Cable Diameters (DC)</b>	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	22	24	26	28				
PV 2.300	300.520.500.220.480.	15,5	Drum Alu compact W x H x D = 300 x 520 x 500 Core diametre.: 220 Outer diametre.: 480	5700	4100	3200	2100	1300	800	500	300	200	100	000	000	000	000	000	000	000	000	000				
PV 2.400	400.520.500.220.480.	17,0	Drum Alu compact W x H x D = 400 x 520 x 500 Core diametre.: 220 Outer diametre.: 480	93300	67000	50800	33400	21900	13600	8300	5000	3000	2000	1000	0000	0000	0000	0000	0000	0000	0000	0000				
PV 2.500	500.520.500.220.480.	18,5	Drum Alu compact W x H x D = 500 x 520 x 500 Core diametre.: 220 Outer diametre.: 480	129900	93000	70400	46300	30800	19300	11900	7300	4500	2700	1600	900	500	300	100	000	000	000	000				
PV 2.600	600.520.500.220.480.	20,0	Drum Alu compact W x H x D = 600 x 520 x 500 Core diametre.: 220 Outer diametre.: 480	164900	119000	90000	59500	39000	25000	15600	9600	5800	3500	2100	1200	700	400	200	100	000	000	000				
PV 2.700	700.520.500.220.480.	21,5	Drum Alu compact W x H x D = 700 x 520 x 500 Core diametre.: 220 Outer diametre.: 480	200400	141000	106800	70600	46300	30800	19300	11900	7300	4500	2700	1600	900	500	300	100	000	000	000				
PV 2.800	800.520.500.220.480.	23,0	Drum Alu compact W x H x D = 800 x 520 x 500 Core diametre.: 220 Outer diametre.: 480	263700	182000	136000	90600	59500	39000	25000	15600	9600	5800	3500	2100	1200	700	400	200	100	000	000				
			<b>Cable Diameters (DC)</b>	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	22	24	26	28				
PV 3.400	400.620.600.220.580.	20,8	Drum Alu for up to zu ¼ EUPAL W x H x D = 400 x 620 x 600 Core diametre.: 220 Outer diametre.: 580	133400	118500	86000	56300	36400	23800	15000	9200	5600	3400	2000	1200	700	400	200	100	000	000	000				
PV 3.500	500.620.600.220.580.	22,5	Drum Alu W x H x D = 500 x 620 x 600 Core diametre.: 220 Outer diametre.: 580	21500	15100	11900	7800	5100	3300	2000	1200	700	400	200	100	000	000	000	000	000	000	000				
PV 3.600	600.620.600.220.580.	24,0	Drum Alu W x H x D = 600 x 620 x 600 Core diametre.: 220 Outer diametre.: 580	266900	194000	147000	97000	64000	42000	27000	16000	9800	6000	3700	2200	1300	700	400	200	100	000	000				
PV 3.700	700.620.600.220.580.	25,6	Drum Alu W x H x D = 700 x 620 x 600 Core diametre.: 220 Outer diametre.: 580	323600	238000	178000	117000	77000	51000	33000	20000	12000	7000	4300	2600	1500	900	500	300	100	000	000				
PV 3.800	800.620.600.220.580.	27,5	Drum Alu for up to zu ½ EUPAL W x H x D = 800 x 620 x 600 Core diametre.: 220 Outer diametre.: 580	377900	271000	206000	137000	90000	59000	38000	24000	14000	8500	5100	3000	1800	1000	600	300	100	000	000				
			<b>Cable Diameters (DC)</b>	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	22	24	26	28				
PV 8.300	300.820.800.300.780.		Drum Alu W x H x D = 300 x 820 x 800 Core diametre.: 300 Outer diametre.: 780	7500	5300	3900	2700	1700	1100	700	430	260	160	100	60	30	10	00	00	00	00	00				
PV 8.400	400.820.800.300.780.		Drum Alu W x H x D = 400 x 820 x 800 Core diametre.: 300 Outer diametre.: 780	8300	5900	4300	3000	1900	1200	800	490	300	180	110	60	30	10	00	00	00	00	00				
PV 8.500	500.820.800.300.780.		Drum Alu W x H x D = 500 x 820 x 800 Core diametre.: 300 Outer diametre.: 780	8800	6300	4500	3100	2000	1300	850	510	310	190	110	60	30	10	00	00	00	00	00				
PV 8.600	600.820.800.300.780.		Drum Alu W x H x D = 600 x 820 x 800 Core diametre.: 300 Outer diametre.: 780	10400	7500	5400	3700	2400	1500	950	580	350	210	120	70	40	20	10	00	00	00	00				
PV 8.700	700.820.800.300.780.		Drum Alu W x H x D = 700 x 820 x 800 Core diametre.: 300 Outer diametre.: 780	12800	9200	6600	4500	2900	1800	1100	670	400	240	140	80	40	20	10	00	00	00	00				
PV 8.800	800.820.800.300.780.		Drum Alu W x H x D = 800 x 820 x 800 Core diametre.: 300 Outer diametre.: 780	15200	10800	7800	5300	3400	2200	1400	850	510	310	190	110	60	30	10	00	00	00	00				
Cable Cube	350.500.480.220.440	13,6	Case drum Alu W x H x D = 350 x 500 x 480 Core diametre.: 220 Outer diametre.: 440	7100	5200	3800	2600	1700	1100	700	430	260	160	100	60	30	10	00	00	00	00	00				